



- 3 ¾ Digit LCD
- Max display 3999 counts
- 600 A AC TRMS
- 600 VDC, 600 VAC TRMS
- 40 MΩ, 10 MHz, 750°C
- 100 uF, duty cycle
- Diode, Continuity, data hold, backlight
- Jaw Size 36mm

Technical Specifications

Function	Range	Accuracy
DC voltage	400m-600V	For 400mV±(0.8%+5dgt), For 4/40/400/600V±(0.8%+2dgt),
AC voltage	400m-600V TRMS	For 400mV±(2.0%+5dgt), For 4/40/400/600V±(1.2%+3dgt),
OHM	400-40MΩ	For 400/4k/40k/400k/4M/40MΩ ±(1.5%+3dgt)
ACA	400-600A TRMS	For 400/600A±(2.0%+5dgt)
Frequency	0 to 10MHz	For 0 to 10MHz ±(0.8% +5dgt)
Temperature	0°C~750°C	For 0 to 400°C ±(1.0%+3dgt), For 0 to 401-750°C ±(2.0%+3dgt),
Duty cycle	0.01- 99.9 %	For 0.01- 99.9 % ±(1.0%)
Capacitance	40nF- 100uF	For 40nF/400nF/4μF/40μF/100μF±(5%+8dgt)
Power supply	(AAA) 1.5V×2	
Max display	3999	
Diode test	YES	
Continuity Buzzer	YES	
Backlight	YES	
Data hold	YES	
Weight	205g	
Dimension	190L×69W×27Hmm	
Standard Accessories	Carrying case, Test leads, thermocouple; manual,	

DOT TECHNOLOGIES

(An ISO 9001:2008 Certified Company)

25, Victoria Road, Victoria Layout, Bangalore-560047 INDIA Email: info@dottech.in, web: www.dottech.in

Phone: 080 25549344 / 080 25542753 / 08970010661 / 09844010308 Fax: 080 25542753

