



- 3 ½ Digit LCD
- Max display 1999 counts
- 130 d B
- Auto power off

## Technical Specifications

Function	Range
<b>MEASUREMENT RANGE</b>	35 to 130 DB
<b>LEVEL RANGE</b>	Lo : 35 to 100 d B Hi : 65 to 130 d B
<b>RESOLUTION</b>	0.1 DB
<b>ACCURACY</b>	± 1.5 d B (under reference condition)
<b>FREQUENCY</b>	31.5 HZ to 8 K HZ
<b>MICROPHONE</b>	½ inch Electret condenser type
<b>CALIBRATION</b>	Electrical calibration with the internal oscillator (1K Hz sine wave)
<b>TIME WEIGHTING</b>	Fast (125 m S), Slow (1 sec)
<b>DISPLAY</b>	4 Digits LCD 1999 Counts
<b>Display Up data</b>	0.5 Sec
<b>OVER RANGE INDICATION</b>	" 1 " Figures only on display
<b>POLARITY</b>	" - " Displayed for negative polarity
<b>LOW BATTERY</b>	Yes
<b>Alarm function</b>	"OVER" is show when input is out of range
<b>AUX. POWER</b>	9V battery
<b>SIZE (mm)</b>	55(W) x 210(L) x 32(H) mm
<b>WEIGHT</b>	230 gm
<b>Accessories</b>	Operation manual, carry case

## DOT TECHNOLOGIES

(An ISO 9001:2008 Certified Company)

25, Victoria Road, Victoria Layout, Bangalore-560047 INDIA Email: [info@dottech.in](mailto:info@dottech.in), web: [www.dottech.in](http://www.dottech.in)  
Phone: 080 25549344 / 080 25542753 / 08970010661 / 09844010308 Fax: 080 25542753